# Battery Operated Grease-Gun 18 V Li-Ion AMPShare - Powered by BOSCH

Description Images and specifications can be subject to change without notice Part No. EUR / Unit



#### Accu-Greaser 18 V Basic-S

Battery operated grease-gun 18V Li-Ion,

suitable for 400 g pull-off cartridge according to DIN 1284.

The version features a powerfull drive unit that reaches peak pressure rates well above 700 bar. The greaser drive unit is equipped with an electric overload protection.

- max. flow rate approx. 120 ccm/min.
- LED lightbeam
- grease barrel for 400 g pull-off cartridges or 500 ccm bulk grease, cartridge not included
- filling-/ and air venting nipple
- high-pressure safety rubber-hose (1.650 bar b.p. ), lenght 750 mm, incl. 4-jaw hydraulic safety-coupler R1/8"
- carry-along case with cavities for spare battery and spare cartridge

### Basic version does neither include AMPShare battery pack, nor AMPShare charger

Accu-Greaser 18 V Basic-S 34 240 08 328.00

# Accu-Greaser 18 V Basic-LS

Battery operated grease-gun 18V Li-Ion,

# suitable for 400 g Lube-Shuttle® cartridge,

for item description please see above. Version comes with cartridge protection tube for 400 g Lube-Shuttle® cartridge and plug to replace filling-/air venting nipple (vacuum principle).

Accu-Greaser 18 V Basic-LS 34 241 07 328.00

#### Accu-Greaser 18 V Basic-SP

Battery operated grease-gun 18V Li-lon,

### suitable for 500 g screw-cap cartridges,

for item description please see above. Version comes with protection tube for 500 g screw-cap cartridges and plug instead of filling-/air venting nipple (vacuum principle).

Accu-Greaser 18 V Basic-SP 34 242 06 364.20

# Accu-Greaser 18 V Basic-S-LS

Battery operated grease-gun 18V Li-Ion, suitable for

- 400 g pull-off cartridges according to DIN 1284 AND
- 400 g Lube-Shuttle® cartridges,

for item description see above. Version comes with grease barrel for 400 g pull-off cartridge AND cartridge protection tube for 400 g Lube-Shuttle® cartridge and plug to replace filling-/air venting nipple.

The filling and venting nipple must be replaced by the plug when using screw-cap cartridges (vacuum principle)!

Accu-Greaser 18 V Basic-S-LS 34 243 05 339,80

### Accu-Greaser 18 V Basic-S-LSP

Battery operated grease-gun 18V Li-Ion, suitable for

- 400 g pull-off cartridges according to DIN 1284 AND
- 400 g Lube-Shuttle® cartridges AND
- 500 g screw-neck cartridges (LS 500),

for item description see above. Version comes with grease barrel for 400 g pull-off cartridge

AND cartridge protection tube for 400 g Lube-Shuttle® cartridge AND adaptor for 500 g screw-cap cartridges and plug to replace filling-/air venting nipple.

The filling and venting nipple must be replaced by the plug when using screw-cap cartridges (vacuum principle)!

Accu-Greaser 18 V Basic-S-LSP 34 244 04 372,10



# **Basic-Line**

- battery pack not included
  - charger not included









# Battery Operated Grease-Gun 18 V Li-Ion AMPShare - Powered by BOSCH

Description Images and specifications can be subject to change without notice Part No. EUR / Unit



#### Accu-Greaser 18 V Premium-S

Battery operated grease-gun 18V Li-Ion,

suitable for 400 g pull-off cartridge according to DIN 1284.

The version features a powerfull drive unit that reaches peak pressure rates well above 700 bar. The greaser drive unit is equipped with an electric overload protection.

- max. flow rate approx. 120 ccm/min.
- LED lightbeam
- grease barrel for 400 g pull-off cartridges or 500 ccm bulk grease, cartridge not included
- filling-/ and air venting nipple
- high-pressure safety rubber-hose (1.650 bar b.p.), lenght 750 mm, incl. 4-jaw hydraulic safety-coupler R1/8"
- carry-along case with cavities for spare battery and spare cartridge

# Premium version includes AMPShare battery pack GBA 18V 2.0 Ah and AMPShare charger GAL 18V-40

Accu-Greaser 18 V Premium-S 34 240 15 430.00

#### **Accu-Greaser 18 V Premium-LS**

Battery operated grease-gun 18V Li-Ion,

#### suitable for 400 g Lube-Shuttle® cartridge,

for item description please see above. Version comes with cartridge protection tube for 400 g Lube-Shuttle® cartridge and plug to replace filling-/air venting nipple (vacuum principle).

Accu-Greaser 18 V Premium-LS 34 241 14 430.00

#### **Accu-Greaser 18 V Premium-SP**

Battery operated grease-gun 18V Li-lon,

# suitable for 500 g screw-cap cartridges,

for item description please see above. Version comes with protection tube for 500 g screw-cap cartridges and plug instead of filling-/air venting nipple (vacuum principle).

Accu-Greaser 18 V Premium-SP 34 242 13 466.20

# Accu-Greaser 18 V Premium-S-LS

Battery operated grease-gun 18V Li-Ion, suitable for

- 400 g pull-off cartridges according to DIN 1284 AND
- 400 g Lube-Shuttle® cartridges,

for item description see above. Version comes with grease barrel for 400 g pull-off cartridge AND cartridge protection tube for 400 g Lube-Shuttle® cartridge and plug to replace filling-/air venting nipple.

The filling and venting nipple must be replaced by the plug when using screw-cap cartridges (vacuum principle)!

Accu-Greaser 18 V Premium-S-LS 34 243 12 441,80

### Accu-Greaser 18 V Premium-S-LSP

Battery operated grease-gun 18V Li-Ion, suitable for

- 400 g pull-off cartridges according to DIN 1284 AND
- 400 g Lube-Shuttle® cartridges AND
- 500 g screw-neck cartridges (LS 500),

for item description see above. Version comes with grease barrel for 400 g pull-off cartridge

AND cartridge protection tube for 400 g Lube-Shuttle® cartridge AND adaptor for 500 g screw-neck cartridges and plug to replace filling-/air venting nipple.

The filling and venting nipple must be replaced by the plug when using screw-cap cartridges (vacuum principle)!

Accu-Greaser 18 V Premium-S-LSP 34 244 11 474.10

# Premium-Line

- AMPShare battery GBA 18 V 2.0 Ah
  - AMPShare charger GAL 18V-40









# Battery Operated Grease-Gun 18 V Li-Ion AMPShare - Powered by BOSCH

**Description**Images and specifications can be subject to change without notice

Part No. EUR / St.

#### Accu-Greaser 18 V Professional-S

Battery operated grease-gun 18V Li-Ion,

suitable for 400 g pull-off cartridge according to DIN 1284.

The version features a powerfull drive unit that reaches peak pressure rates well above 700 bar. The greaser drive unit is equipped with an electric overload protection.

- max. flow rate approx. 120 ccm/min.
- LED lightbeam, shoulder strap
- grease barrel for 400 g pull-off cartridges or 500 ccm bulk grease, cartridge not included
- filling-/ and air venting nipple
- high-pressure safety rubber-hose (1.650 bar b.p. ), lenght 750 mm, incl. 4-jaw hydraulic safety-coupler R1/8"
- carry-along case with cavities for spare battery and spare cartridge

# Version includes AMPShare battery pack GBA 18 V 4.0 Ah and AMPShare charger GAL 18V-40

Accu-Greaser 18 V Professional-S 34 240 22 465,00

#### Accu-Greaser 18 V Professional-LS

Battery operated grease-gun 18V Li-Ion,

#### suitable for 400 g Lube-Shuttle® cartridge,

for item description please see above. Version comes with cartridge protection tube for 400 g Lube-Shuttle® cartridge and plug to replace filling-/air venting nipple (vacuum principle).

Accu-Greaser 18 V Professional-LS 34 241 21 465,00

# Accu-Greaser 18 V Professional-SP

Battery operated grease-gun 18V Li-lon,

# suitable for 500 g screw-cap cartridges,

for item description please see above. Version comes with protection tube for 500 g screw-cap cartridges and plug instead of filling-/ air venting nipple (vacuum principle).

Accu-Greaser 18 V Professional-SP 34 242 20 501,20

# Accu-Greaser 18 V Professional-S-LS

Battery operated grease-gun 18V Li-Ion, suitable for

- 400 g pull-off cartridges according to DIN 1284 AND
- 400 g Lube-Shuttle® cartridges,

for item description see above. Version comes with grease barrel for 400 g pull-off cartridge AND cartridge protection tube for 400 g Lube-Shuttle® cartridge

and plug to replace filling-/air venting nipple.

# The filling and venting nipple must be replaced by the plug when using screw-cap cartridges (vacuum principle)!

Accu-Greaser 18 V Professional-S-LS 34 243 29 476,80

### Accu-Greaser 18 V Professional-S-LSP

Battery operated grease-gun 18V Li-lon, suitable for

- 400 g pull-off cartridges according to DIN 1284 AND
- 400 g Lube-Shuttle® cartridges AND
- 500 g screw-neck cartridges (LS 500),

for item description see above. Version comes with grease barrel for 400 g pull-off cartridge

AND cartridge protection tube for 400 g Lube-Shuttle® cartridge AND adaptor for 500 g screw-cap cartridges

and plug to replace filling-/air venting nipple.

The filling and venting nipple must be replaced by the plug when using screw-cap cartridges (vacuum principle)!

Accu-Greaser 18 V Professional-S-LSP 34 244 28





# **Professional-Line**

- AMPShare battery GBA 18 V 4.0 Ah - AMPShare charger GAL 18V-40 - shoulder strap







# Accessories for Battery Grease-Gun AMPShare - Powered by BOSCH

Description Images and specifications can be subject to change without notice Part No. EUR / Unit





# AMPShare battery pack GBA 18 V - 2.0 Ah

# BOSCH Li-Ion AMPShare battery pack GBA 18 V DC / 2.0 Ah

with LED charge status indicator

Charging time: approx. 80% in 24 min. / 100% in 35 min.

COOLPACK 1.0 technology cools the battery faster and helps to provide longer lifetime.

18V batteries and chargers are compatible with Bosch 18V power tools and cordless products from AMPShare  $^{\text{TM}}$  alliance brands.



# AMPShare battery pack GBA 18 V - 4.0 Ah

BOSCH Li-Ion AMPShare battery pack GBA 18 V DC / 4.0 Ah

with LED charge status indicator

Charging time: approx. 80% in 48 min. / 100% in 65 min.

COOLPACK 1.0 technology cools the battery faster and helps to provide longer lifetime

18V batteries and chargers are compatible with Bosch 18V power tools and cordless products from AMPShare™ alliance brands


AMPShare battery pack GBA 18 V - 4.0 Ah 34 290 27 81.90



BOSCH AMPShare charger GAL 18V-40

with overcharge protection, 220-240 V AC / 50-60 Hz, On/Off-LED, cable 2,0 m with EU flat-plug

18V batteries and chargers are compatible with Bosch 18V power tools and cordless products from AMPShare™ alliance brands



for Accu-Greaser 18 V

High pressure safety hose ø 13mm, burst pressure 1,650 bar (double steel wire braided)

RH-75 750mm thread R 1/8", without coupler	32 585 80	25,40
RH-75C 750mm thread R 1/8", with coupler	32 589 48	32,30

#### Lance with lubricating brush

The lance assembly includes a lubricating brush, a highpressure handle and a z-swivel joint. It comes with separate 400/800 mm pipe segments that can be bolted by a hex-nut. The unit can directly be tied to the 750 mm high-pressure Accu-Greaser rubber hose. The lance is equipped with a PA6 nylon brush (R1/8"), with a  $\emptyset$  25 mm brush, to lubricate surfaces like open gears, chains, linear and glide rails, train-tracks, etc.

For spare brush see page 54

Lance with lubricating brush and handle









