



# G-Mini™ Compact Pump

Small size. Big value. Huge Impact



PROVEN QUALITY. LEADING TECHNOLOGY.

Make the most of your space, budget and machines. The new full-featured G-Mini offers reliable lubrication with a small footprint to suit more types of machine. Use it to simplify everyday maintenance, extend life cycles and optimise uptime. It's rugged and tough, perfect for handling the daily 24/7 rigours of any job big or small. Best of all, it comes with a modest price tag – boosting your productivity and profitability.

**Follower Plate and Stir Paddle**

This unique combination combats oil separation while ensuring the pump element "loading chamber" is always full.

**Multiple Reservoir Options**

Comes in both 0.5-litre and 1-litre sizes.

**Patent-Pending Heater**

Pump grease down to -40° C/F when ordered with the heater option.

**Up to Two Pump Elements**

4 cm<sup>3</sup>/min (0.25 in<sup>3</sup>/min)  
280 bar (4,100 psi)

**M12 Input**

M12 cycle or proximity switch input standard on all pumps with a controller.

**Two Control Options**

**No Controller:** pair with either an external controller or PLC.

**Controller:** Easy-to-program controller can be utilised for both time-based and cycle-based systems and provides low-level alert and alarm.

**5-Wire CPC Power Cable**

Multi-function cable supplies power to the pump, pairs with a remote manual run button, and provides low-level or cycle fault output.

**Rugged Construction**

Designed to withstand the harshest of environments; IP69K rated.



► **Typical Applications**

- Wind energy
- Food and beverage
- Off-road mobile equipment
- On-road mobile equipment



## ► Technical Specifications

<b>Power source</b>	12 VDC or 24 VDC
<b>Handles fluids</b>	Grease NLGI 000 to #2
<b>System</b>	Pump to point or series progressive
<b>Operating temperature</b>	-40°C to 70°C (-40°F to 158°F)
<b>Reservoir size</b>	0.5 L / 1 L
<b>Control option</b>	No control, controller (time or cycle)
<b>Pump elements</b>	Up to 2
<b>Output pressure</b>	280 bar (4,100 psi)
<b>Pump output</b>	4 cm <sup>3</sup> /min (0.25 in <sup>3</sup> /min)
<b>Pump outlet</b>	1/4-18 NPSF, mates with 1/4-18 NPT male fittings
<b>Protection grade</b>	IP69K



## ► Ordering Information

### Pumps

G-Mini pumps **do not** come with power cables. See Accessories below for power cable options.

Controller Option	Voltage	Reservoir Size	Heater	Part Number	Part Description
No Controller	12V	0.5L	No	25R809	0.5 Litre, 12 Volt G-Mini Pump
		1L	No	25R802	1 Litre, 12 Volt G-Mini Pump
	24V	0.5L	No	25R807	0.5 Litre, 24 Volt G-Mini Pump
		1L	No	25R800	1 Litre, 24 Volt G-Mini Pump
Controller	12V	0.5L	No	25R810	0.5 Litre, 12 Volt G-Mini Pump with Controller
		1L	No	25R803	1 Litre, 12 Volt G-Mini Pump with Controller
			Yes	25R806	1 Litre, 12 Volt G-Mini Pump with Controller and Heater
	24V	0.5L	No	25R808	0.5 Litre, 24 Volt G-Mini Pump with Controller
		1L	No	25R801	1 Litre, 24 Volt G-Mini Pump with Controller
			Yes	25R804	1 Litre, 24 Volt G-Mini Pump with Controller and Heater

### Accessories

Additional accessories can be found in the Graco Industrial Lubrication Equipment (ILE) Buyer's Guide (p/n 340821).

Part Number	Description
127783*	3-Wire CPC Power Cable 4.6 mm
127780*	5-Wire CPC Power Cable 4.6 mm
25C981	12V Manual Run Button (5-Wire CPC power cable required)
25C982	24V Manual Run Button (5-Wire CPC power cable required)
26C825	Direct Mount CSP Bracket
26C826	Universal Mounting Bracket (allows for drop-in replacement of competition)
17L879	Graco CSP Solid State Proximity Switch (DC PNP)
17R703	1 ft Proximity Switch Cable, M12 female straight to M12 male straight cable
124333	16.5 ft Proximity Cable, M12 female straight to M12 male straight
26A910	4,000 PSI Pressure Relief Kit (1/4 NPT to 1/8 NPT reducer bushing, 1/8 NPT branch T-fitting, 4,000 PSI pressure relief valve)
25N827	Pump Element Kit (add a second pump element or replace existing element)
24M644	High Capacity Fill Stud Quick Disconnect and Dust Cover
247886	Manual Fill Pump – fits 5 gallon or 35 lb pail (requires 24M644)

\*G-Mini pumps do not come with power cables. Power cables needed for installation.



## ABOUT GRACO

Founded in 1926, Graco is a world leader in fluid handling systems and components. Graco products move, measure, control, dispense and apply a wide range of fluids and viscous materials used in vehicle lubrication, commercial and industrial settings.

The company's success is based on its unwavering commitment to technical excellence, world-class manufacturing and unparalleled customer service. Working closely with qualified distributors, Graco offers systems, products and technology that set the quality standard in a wide range of fluid handling solutions. Graco provides equipment for spray finishing, protective coating, paint circulation, lubrication and dispensing sealants and adhesives, along with power application equipment for the contractor industry. Graco's ongoing investment in fluid management and control ensures the continued provision of innovative solutions to a diverse global market.

## GRACO LOCATIONS

### MAILING ADDRESS

P.O. Box 1441  
Minneapolis, MN 55440-1441  
Tel: 612-623-6000  
Fax: 612-623-6777

### AMERICAS

#### MINNESOTA

Worldwide Headquarters  
Graco Inc.  
88-11th Avenue N.E.  
Minneapolis, MN 55413

### EUROPE

#### BELGIUM

European Headquarters  
Graco Distribution BV  
Industrieterrein-Oude Bunders  
Slakweidestraat 31  
3630 Maasmechelen  
Belgium  
Tel: 32 89 770 700  
Fax: 32 89 770 777

### ASIA PACIFIC

#### AUSTRALIA

Graco Australia Pty Ltd.  
Suite 17, 2 Enterprise Drive  
Bundoora, Victoria 3083  
Australia  
Tel: 61 3 9468 8500  
Fax: 61 3 9468 8599

#### CHINA

Graco Hong Kong Ltd.  
Shanghai Representative Office  
Building 7  
1029 Zhongshan Road South  
Huangpu District  
Shanghai 200011  
The People's Republic of China  
Tel: 86 21 649 50088  
Fax: 86 21 649 50077

#### INDIA

Graco Hong Kong Ltd.  
India Liaison Office  
Room 432, Augusta Point  
Regus Business Centre 53  
Golf Course Road  
Gurgaon, Haryana  
India 122001  
Tel: 91 124 435 4208  
Fax: 91 124 435 4001

#### JAPAN

Graco K.K.  
1-27-12 Hayabuchi  
Tsuzuki-ku  
Yokohama City, Japan 2240025  
Tel: 81 45 593 7300  
Fax: 81 45 593 7301

#### KOREA

Graco Korea Inc.  
38, Samsung 1-ro 1-gil  
Hwaseong-si, Gyeonggi-do,  
18449  
Republic of Korea  
Tel: 82 31 8015 0961  
Fax: 82 31 613 9801

All written and visual data contained in this document is based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Graco is ISO 9001 certified.



**Europe**  
+32 89 770 700  
FAX +32 89 770 777  
WWW.GRACO.COM